

Magnetic switches 磁性开关

■ GR Cylindrical type 圆柱型

- Cylindrical brass body
- M8x45,M12x50 diameter
- NO,NC,CO(NO+NC) output
- Front side switching
- PVC cable 2m

Gr12-

Gr08-



■ GS Rectangle type 方型

- Plastic case
- Many varieties of sensors
- NO,NC,CO(NO+NC) output
- PVC cable 2m

Gs25	Gs56	Gs28	Gs33	Gs51
尺寸: 25X15X6mm	尺寸: 56X21X10mm	尺寸: 28X19X6.5mm	尺寸: 34X12X10mm	尺寸: 51X10X11mm
Gs27	Gs40	Gs401	Gs35	Gs23
尺寸: 27X13X11mm	尺寸: 40X12X8mm	尺寸: 40X20X10mm	尺寸: 35X18X12mm	尺寸: 23X7X10mm
Gs22	Gs335	Gs26	Gs30	Gs341
尺寸: 22X7X12mm	尺寸: 33.5X15X15mm	尺寸: 26X10X8mm	尺寸: 30X6X5mm	尺寸: 34X16X11mm

Magnetic switches 磁性开关

Ordering information 圆柱型


GR08-1A250K1

- Output: K1---NO,K2---NC,K3---CO(NO+NC) 输出构成
- Contact capacity: 1A250---1A/250V, 0.5A100--- 0.5A/100V 触点容量
- Serial number: 08---side length 设计序号
- Appearance: GR---cylindrical case, GS-rectangle case 外型分类


Specification规格

Contact 触点容量	1A/250V	0.5A/100V
switching voltage 开关电压	Min.250VAC	DC 100VDC
breakdown voltage 最大崩溃电压	Max. 1000VDC	Max. 200VDC
switching current 最大开关电流	Max. NO:1A NC: 0.5A	Max. NO:0.5A
carry current 最大负载电流	Max.NO: 2.5A NC: 1A	Max. NO:1A
contact rating 最大功率	50W	12W
response frequency 最大频率	10HZ	
insulation resistance 绝缘电阻	Min.50MΩ	
dielectric strength 耐电压	1500VAC 50/60HZ for 1 minute	
operating temperature 环境温度	-25 to 75℃	
protection 保护结构	IP67 (IEC)	
material 材料	Case: brass or plastic, cable:PVC	


Wiring diagrams 接线图



Output NO



Output NC



Output CO(NO+NC)